



Quality Products. Service Excellence.

# Horizontal Hinged Cable Manager *PCMDD Series*

## Features



- Constructed in 16-gauge steel.
- Continuous hinged door with magnetic closure strip.
- Four oblong openings (3.5" x 1.56") top & bottom - allowing for cable exit top and/or bottom.
- Openings in the rear for cable entry.
- Designed to fit standard 19" rails.
- Finished in textured black powder paint.
- Requires mounting hardware.
- RoHS and REACH compliant.
- Manufactured in North America.



## Help us improve the PCMDD Series

We're considering adding additional sizes. Would you prefer a deeper depth manager? \*

- Current depth is fine
- Five (5) inch
- Seven (7) inch
- Greater than seven (7) inch

## Gallery



## Accessories

- Mounting Hardware

Part No.	Overall Dimensions			Rack Units	Usable Dimensions		
	Height	Width	Depth		Height	Width	Depth
PCMDD19001BK1	1.72	19.00	2.71	1U	1.25	17.62	2.50
PCMDD19003BK1	3.47	19.00	2.71	2U	3.00	17.62	2.50
PCMDD19005BK1	5.22	19.00	2.71	3U	4.75	17.62	2.50

## Estimated Cable Fill Capa

Rack	Description	Estimated Cable Fill (100% Fill Ratio)
------	-------------	--

**Contact our Technical Sales Team**

Units	Description	Quantity	Recommended Cable Fill (50% Fill Ratio)	Maximum Cable Fill (100% Fill Ratio)
1U	Channel Opening	1	34	15
	Top/Bottom Opening	2 x 4 = 8	43	19
	Rear Pass Through	0	n/a	n/a
2U	Channel Opening	1	68	30
	Top/Bottom Opening	2 x 4 = 8	43	19
	Rear Pass Through	4	32	14
3U	Channel Opening	1	103	46
	Top/Bottom Opening	2 x 4 = 8	43	19
	Rear Pass Through	4	32	14

Cable fill capacity will vary based on the cable manufacturer.

*Data subject to change without notice*

© 2018. Hammond Manufacturing Ltd. All rights reserved.

**Contact our Technical Sales Team**