

8502SCA2V02S

Non-Reversing Contactor, Size 1, 3-Pole, NEMA 12
+Options



Main

| | |
|--------------------------------|--|
| Product or component type | Contacteur |
| Range of product | 8502S |
| Control circuit | Separate control circuit |
| [Uc] control circuit voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Contactor application | Non-reversing |
| [In] rated current | 27 A |
| Poles description | 3P |
| Network number of phases | 3 phases |
| Rated power in HP | 7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC |
| [Ue] rated operational voltage | 600 V AC |
| Control type | No control units |
| Local signalling | No indicator |
| Auxiliary contact composition | Without |
| Provided equipment | Fuse not supplied |
| Electrical connection | Screw clamp terminals |
| NEMA degree of protection | NEMA 12 painted sheet steel |
| Product certifications | CSA UL listed |
| NEMA size | 1 |
| Height | 324 mm |
| Depth | 217 mm |
| Width | 162 mm |

Complementary

Environment

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1545 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.