# PRODUCT SPECIFICATIONS / INFO





# **515PR**

## Description

15 Amp, 125 Volt, NEMA 5-15P, 2P, 3W, Plug, Straight Blade, Commercial Grade, Rubber, Grounding - Black

#### **Product Features**

Grounding: Grounding Feature: Rubber Amperage: 15 Amp Voltage: 125 Volt NEMA: 5-15P Pole: 2 Wire: 3

Cord Range: .245 - .655 Wire Gauge: 18-12 AWG

Blades/Contacts: Brass

Body Material: EPTR Rubber Assembly Screws: Steel, Zinc Plated

Color: Black

Standards and Certifications: UL/CSA

Warranty: 10-Year Limited




**NEMA: 5-15P** 



#### **Features and Benefits**

- Triple-drive heady screws Standard, Phillips, Robertson
- NEMA configuration number & rating molded on face of device for easy identification
- · Deep-slotted, backed out terminal screws draw backwire clamps securely for maximum conductivity
- · Husk & module keyed for easy alignment during wiring
- Built-in cord grip adjusts automatically for use with No. 18-3 through No. 12-3 cords
- Designed to stand up to rough use
- · No internal metal parts exposed
- · Elastomeric husk provides added protection against dirt and moisture entry into the back wire port
- Designed to operate in the widest possible temperature range
- Backed by a Limited 10-Year Warranty

# Wiring Diagram



5-15R

## SPECIFICATION SUBMITTAL

ı	JOB NAME:	CATALOG NUMBERS:
	JOB NUMBER:	

Leviton Manufacturing Co., Inc.

59-25 Little Neck Parkway, Little Neck, NY 11362-2591

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-


Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Clairé, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800 -824-3005

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx



©2007 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

