

## Product datasheet

### Characteristics

# 8502SDO1V02S

Non-Reversing Contactor, Size 2, 2-Pole, Open Style  
+Options



### Main

Product or component type	Contacteur
Range of product	8502S
Control circuit	Separate control circuit
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Contactor application	Non-reversing
[In] rated current	45 A
Poles description	2P
Network number of phases	1 phase
Rated power in HP	7.5 HP 230 V AC 3 HP 115 V AC
[Ue] rated operational voltage	600 V AC
Control type	No control units
Local signalling	No indicator
Auxiliary contact composition	Without
Provided equipment	Fuse not supplied
Electrical connection	Screw clamp terminals
NEMA degree of protection	Not rated (open device)
Product certifications	CSA UL listed
NEMA size	2
Height	130 mm
Depth	125 mm
Width	125 mm

### Complementary

### Environment

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.