

Product datasheet
Characteristics

8536SCG3V08

Non-Reversing Starter Size 1, 3-Pole, Melting Alloy Overload, Nema 1



Main

Product or component type	Starter
Range of product	S
Control circuit	Common control circuit

Complementary

[Uc] control circuit voltage	208 V AC 60 Hz
Motor starter type	Non reversing
[In] rated current	27 A
Poles description	3P
Network number of phases	3 phases
Rated power in HP	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC
[Ue] rated operational voltage	600 V AC
Control type	No control units
Thermal overload type	Melting alloy 3 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	1
Height	254 mm
Depth	141 mm
Width	152 mm

Environment

NEMA degree of protection	NEMA 1 painted sheet steel
product certifications	CSA NEMA UL listed

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.