

Product datasheet
Characteristics

TVS8EBA24A

EBA TVSS, 600Y/347V, 3 ph, 4 wire, 240kA

Main

Device short name	EBA
Provided equipment	Alarm for enable/disable switch
Range of product	Surgelogic

Complementary

[Ue] rated operational voltage	600Y/347 V AC
Device mounting	Flush Surface
Enclosure material	Painted steel
Local signalling	Green for normal per phase Red for fault per phase
Mounting location	Service entrance
Network number of phases	3 phases
Short-circuit protection	200 kA
Surge current	<= 240 kA per phase
Wiring configuration	3-wire 4-wire

Environment

NEMA degree of protection	NEMA 3R/12
standards	UL 1283 ANSI/IEEE C62.41 ANSI/IEEE C62.45 UL 1449 : ed. 2 UL Category Section 37.3

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.