

**Product datasheet**  
Characteristics

**NC040**  
STAB-LOK CIRCUIT BREAKER 120V 40A 1P



**Main**

|                                |                           |
|--------------------------------|---------------------------|
| Range of product               | Stab-lok                  |
| Product or component type      | Miniature circuit-breaker |
| [In] rated current             | 40 A                      |
| [Ue] rated operational voltage | 120 V AC                  |
| Poles description              | 1P                        |
| Breaking capacity              | 10 kA                     |

**Complementary**

|                       |                          |
|-----------------------|--------------------------|
| Mounting mode         | Plug-in                  |
| Electrical connection | Screw connector          |
| AWG gauge             | AWG 14...AWG 10 (copper) |

**Environment**

|                        |     |
|------------------------|-----|
| product certifications | CSA |
|------------------------|-----|

**Offer Sustainability**

|                          |                           |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW)   | Will not be Compliant     |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.