



### Main

Range of product	Homeline
Product or component type	Miniature circuit-breaker
[In] rated current	30 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Plug-on
Poles description	2P
Short-circuit current	10 kA
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Screw clamp terminals

### Complementary

Number of spaces required	2
AWG gauge	AWG 14...AWG 8 (aluminium/copper)

### Environment

product certifications	CSA
ambient air temperature for operation	40 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.